

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.



The Delphion
Integrated
View

Other Views:
[INPADOC](#)

Title: **JP7272702A2: MANUFACTURE OF RING-SHAPED GASKET OF MANGANESE DRY BATTERY**

► [Want to see a more descriptive title highlighting what's new about this invention?](#)

Country: **JP Japan**
Kind: **A**

Inventor(s): **SUZUKI YUKIFUMI
MURATA CHIIRO
MURAKOSHI MITSUO
IZUMI AKIHIDE
NISHIO MASATAKE**

Applicant/Assignee:
**Inquire Regarding
Licensing**

FUJI ELELCTROCHEM CO LTD

[News, Profiles, Stocks and More about this company](#)

Issued/Filed Dates:

Oct. 20, 1995 / March 30, 1994

Application Number:

JP1994000061135

IPC Class:

H01M 2/08;

Priority Number(s):

March 30, 1994 JP1994000061135


Abstract:

Purpose: To enhance electrolyte leakage resistance of a manganese dry battery.

Constitution: A negative terminal plate 10 and a ring-shaped gasket 11 are arranged in order on the bottom of a cylindrical zinc can 1 with bottom, and the outer circumference of the zinc can 1 is covered with a heat shrinkable resin tube 9 so that the gasket 11 is covered with the circumferential edge of the tube 9, and an outer jacket 12 is fitted to the outer circumference of the tube 9 so that the end of the outer jacket 2 fastens the terminal plate 10 and the gasket 11 through the tube 9. The ring-shaped gasket 11 is manufactured in such a way that a paper material whose density is 0.5-0.6g/cm³ and air permeability is 6-10 seconds is dried until the moisture content becomes 4% or less, then this paper material is impregnated with water repellent material of a mixture of polybutene, paraffine wax, and polyethylene so that the impregnated content becomes 40-wt.% or more. Since the impregnated content of the water repellent material is 40wt.% or more, the electrolyte leakage resistance of a manganese dry battery is surely maintained.

COPYRIGHT: (C)1995,JPO

► [See a clear and precise summary of the whole patent, in understandable terms.](#)



[View
Image](#)

1 page



Family: [Show known family members](#)

Other Abstract Info: DERABS C96-002616 DERC96-002616

Foreign References: No patents reference this one



Nominate this
for the Gallery...

[Subscribe](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [FAQ](#) | [Site Map](#) | [Help](#) | [Contact Us](#)

© 1997 - 2002 Delphion Inc.



(19)

(11) Publication number: **07272702 A**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **06061135**(51) Intl. Cl.: **H01M 2/08**(22) Application date: **30.03.94**

(30) Priority:

(43) Date of application
publication: **20.10.95**(84) Designated contracting
states:(71) Applicant: **FUJI ELELCTROCHEM CO LTD**(72) Inventor: **SUZUKI YUKIFUMI
MURATA CHIHIRO
MURAKOSHI MITSUO
IZUMI AKIHIDE
NISHIO MASATAKE**

(74) Representative:

**(54) MANUFACTURE OF
RING-SHAPED GASKET OF
MANGANESE DRY
BATTERY**

(57) Abstract:

PURPOSE: To enhance electrolyte leakage resistance of a manganese dry battery.

CONSTITUTION: A negative terminal plate 10 and a ring-shaped gasket 11 are arranged in order on the bottom of a cylindrical zinc can 1 with bottom, and the outer circumference of the zinc can 1 is covered with a heat shrinkable resin tube 9 so that the gasket 11 is covered with the circumferential edge of the tube 9, and an outer jacket 12 is fitted to the outer circumference of the tube 9 so that the end of the outer jacket 2 fastens the terminal plate 10 and the gasket 11 through the tube 9. The ring-shaped gasket 11 is manufactured in such a way that a paper material whose density is 0.5-0.6g/cm³ and air permeability is 6-10 seconds is dried until the moisture content becomes 4% or less, then this

paper material is impregnated with water repellent material of a mixture of polybutene, paraffine wax, and polyethylene so that the impregnated content becomes 40-wt.% or more. Since the impregnated content of the water repellent material is 40wt.% or more, the electrolyte leakage resistance of a manganese dry battery is surely maintained.

COPYRIGHT: (C)1995,JPO

